



1 1/2" DRIVE SOCKETS & ATTACHMENTS

6 Point Deep Length - Impact Black Industrial Finish

	Hex Size	6 Point Part No.	Overall Length in. a	Drive End in. b	Hex End in. c	Taper Length in. d	Bolt Clearance in. e
Style I	15/16"	8-642L	4.50	3.25	2.37	1.25	1.09
	13/8"	8-644L	4.53	3.38	2.52	2.4	1.3
	17/16"	8-646L	4.53	3.38	2.64	2.4	1.38
	1 1/2"	8-648L	4.53	3.38	2.68	2.4	1.42
	15/8"	8-652L	4.53	3.38	2.83	2.4	1.54
	1 11/16"	8-654L	4.53	3.38	2.91	2.4	1.57
	13/4"	8-656L	4.53	3.38	2.95	2.4	1.65
	1 13/16"	8-658L	4.53	3.38	3.07	2.4	1.69
	17/8"	8-660L	4.53	3.38	3.15	2.4	1.73
	1 15/16"	8-662L	4.53	3.38	3.19	2.4	1.77
	2"	8-664L	5.31	3.38	3.27	3.19	1.77
Style II	2 1/16"	8-666L	5.51	3.38	3.31	3.39	1.85
	2 1/8"	8-668L	5.51	3.38	3.39	—	1.93
	2 3/16"	8-670L	5.51	3.38	3.46	—	2.01
	2 1/4"	8-672L	5.91	3.38	3.54	—	2.05
	2 5/16"	8-674L	5.91	3.38	3.62	—	2.13
	2 3/8"	8-676L	5.91	3.38	3.7	—	2.17
	2 7/16"	8-678L	5.91	3.38	3.78	—	2.24
	2 1/2"	8-680L	5.91	3.38	3.86	—	2.28
	2 9/16"	8-682L	5.91	3.38	3.94	—	2.36
	2 5/8"	8-684L	5.91	3.38	4.02	—	2.4
	2 11/16"	8-686L	5.91	3.38	4.09	—	2.48
	2 3/4"	8-688L	6.3	3.38	4.17	—	2.56
	2 13/16"	8-690L	6.3	3.38	4.25	—	2.6
	2 7/8"	8-692L	6.3	3.38	4.29	—	2.68
	2 15/16"	8-694L	6.69	3.38	4.49	—	2.76
	3"	8-696L	6.69	3.38	4.49	—	2.8
	3 1/16"	8-698L	6.69	3.38	4.57	—	2.87
	3 1/8"	8-6100L	6.69	3.38	4.65	—	2.93
	3 3/16"	8-6102L	6.69	3.38	4.92	—	3
	3 1/4"	8-6104L	6.69	3.38	4.92	—	3.05
	3 5/16"	8-6106L	6.69	3.38	4.92	—	3.11
	3 3/8"	8-6108L	6.69	3.38	4.92	—	3.17
	3 7/16"	8-6110L	6.69	3.38	5.04	—	3.23
	3 1/2"	8-6112L	6.69	3.38	5.12	—	3.31
	3 9/16"	8-6114L	6.69	3.38	5.12	—	3.37
	3 5/8"	8-6116L	6.69	3.38	5.12	—	3.43
	3 11/16"	8-6118L	6.69	3.38	5.12	—	3.48
	3 3/4"	8-6120L	7.09	3.74	5.39	—	3.54
	3 13/16"	8-6122L	7.09	3.74	5.51	—	3.62
	3 7/8"	8-6124L	7.09	3.74	5.51	—	3.68
	3 15/16"	8-6126L	7.48	3.74	5.51	—	3.74
	4"	8-6128L	7.48	3.74	5.51	—	3.74
	4 1/16"	8-6130L	7.48	3.74	5.75	—	3.86
	4 3/16"	8-6134L	7.48	3.74	5.91	—	3.98
	4 1/4"	8-6136L	7.48	3.74	5.91	—	4.06
	4 5/16"	8-6138L	7.87	3.74	6.14	—	4.13
	4 3/8"	8-6140L	7.87	3.74	6.3	—	4.13
	4 1/2"	8-6144L	8.27	3.74	6.3	—	4.33
	4 5/8"	8-6148L	8.27	3.74	6.5	—	4.41
	4 3/4"	8-6152L	8.27	3.74	6.61	—	4.53

Federal Spec. U.S. GGG-W-660A ANSI Spec. B107.2



Lock Ring and Pin

Part No.	Description	
PLR150	Locking Ring	.210 x 3.3" O/D
PLP150	Locking Pin	.250 x 2.90" long