


1 1/2" DRIVE SOCKETS & ATTACHMENTS


6 Point Standard Length - Impact Black Industrial Finish

Hex Size	6 Point Part No.	Overall Length in. a	Drive End in. b	Hex End in. c	Taper Length in. d	Bolt Clearance in. e	
1 5/16"	8-642	3.07	3.39	2.36	1.93	1.22	Style I
1 3/8"	8-644	3.07	3.39	2.44	1.75	1.3	
1 7/16"	8-646	3.07	3.39	2.52	1.65	1.34	
1 1/2"	8-648	3.07	3.39	2.6	1.52	1.42	
1 9/16"	8-650	3.07	3.39	2.68	1.38	1.48	
1 5/8"	8-652	3.15	3.39	2.76	1.24	1.54	
1 11/16"	8-654	3.15	3.39	2.8	1.17	1.61	
1 3/4"	8-656	3.31	3.39	2.95	0.9	1.67	
1 13/16"	8-658	3.31	3.39	2.99	0.83	1.69	
1 7/8"	8-660	3.31	3.39	3.07	0.69	1.75	
1 15/16"	8-662	3.43	3.39	3.15	0.55	1.77	
2"	8-664	3.43	3.39	3.23	0.42	1.81	
2 1/16"	8-666	3.43	3.39	3.27	0.35	1.85	
2 1/8"	8-668	3.54	3.39	3.39	—	2.13	Style II
2 3/16"	8-670	3.54	3.39	3.39	—	2.13	
2 1/4"	8-672	3.62	3.39	3.39	—	2.13	
2 5/16"	8-674	3.62	3.39	3.62	—	2.13	
2 3/8"	8-676	3.62	3.39	3.66	—	2.17	
2 7/16"	8-678	3.74	3.39	3.78	—	2.24	
2 1/2"	8-680	3.74	3.39	3.82	—	2.3	
2 9/16"	8-682	3.74	3.39	3.82	—	2.36	
2 5/8"	8-684	3.94	3.39	4.06	—	2.42	
2 11/16"	8-686	3.94	3.39	4.09	—	2.48	
2 3/4"	8-688	3.94	3.39	4.13	—	2.56	
2 13/16"	8-690	4.06	3.39	4.25	—	2.6	
2 7/8"	8-692	4.06	3.39	4.25	—	2.68	
2 15/16"	8-694	4.06	3.39	4.33	—	2.76	
3"	8-696	4.06	3.39	4.33	—	2.8	
3 1/16"	8-698	4.33	3.39	4.53	—	2.85	
3 1/8"	8-6100	4.33	3.39	4.57	—	2.91	
3 3/16"	8-6102	4.33	3.39	4.92	—	2.99	
3 1/4"	8-6104	4.33	3.39	4.92	—	3.05	
3 5/16"	8-6106	4.65	3.39	4.92	—	3.11	
3 3/8"	8-6108	4.65	3.39	4.92	—	3.17	
3 7/16"	8-6110	4.65	3.39	5.04	—	3.23	
3 1/2"	8-6112	4.65	3.39	5.12	—	3.31	
3 9/16"	8-6114	4.65	3.39	5.12	—	3.37	
3 5/8"	8-6116	4.65	3.39	5.12	—	3.43	
3 11/16"	8-6118	4.65	3.39	5.12	—	3.48	
3 3/4"	8-6120	4.65	3.74	5.39	—	3.54	
3 13/16"	8-6122	4.92	3.74	5.51	—	3.62	
3 7/8"	8-6124	4.92	3.74	5.51	—	3.68	
3 15/16"	8-6126	4.92	3.74	5.51	—	3.74	
4"	8-6128	4.92	3.74	5.51	—	3.74	
4 1/16"	8-6130	4.92	3.74	5.75	—	3.86	
4 1/8"	8-6132	4.92	3.74	5.91	—	3.94	
4 3/16"	8-6134	4.92	3.74	5.91	—	3.98	
4 1/4"	8-6136	4.92	3.74	5.91	—	4.06	
4 5/16"	8-6138	4.92	3.74	6.14	—	4.13	
4 3/8"	8-6140	4.92	3.74	6.3	—	4.13	
4 7/16"	8-6142	4.92	3.74	6.3	—	4.17	
4 1/2"	8-6144	5.31	3.74	6.3	—	4.33	
4 5/8"	8-6148	5.31	3.74	6.5	—	4.41	
4 3/4"	8-6152	5.31	3.74	6.61	—	4.53	
4 15/16"	8-6158	6.5	3.25	1.7	1.62	3.5	

Federal Spec. U.S. GGG-W-660A ANSI Spec. B107.2



STYLE I



STYLE II