


**SKIRTBOARD RUBBER 55 DUROMETER**

**Colour**

Black

**Finish**

Smooth

**Physical Characteristics**

Tensile: 500 PSI

Elongation: 300%

Hardness: 55 SHORE "A" +/- 5

Temperature Range: -20°C to 80°C (-4°F to 176°F)

Tolerance on Width: +/- .3937"

**Notes**

Cut to width Skirtboard Rubber is designed for use as skirting on conveyor belt systems. A great cost saving item.

**COMMERCIAL RECYCLED RUBBER ISO/ASTM DESIGNATION= SBR**

Parts No.	Gauge x Width	Length	Wt. Per LN ft.
SKBI55-25-4	1/4" x 4"	50FT	0.63
SKBI55-25-5	1/4" x 5"	50FT	0.79
SKBI55-25-6	1/4" x 6"	50FT	0.95
SKBI55-25-8	1/4" x 8"	50FT	1.25
SKBI55-25-12	1/4" x 12"	50FT	1.89
SKBI55-375-4	3/8" X 4"	50FT	0.94
SKBI55-375-5	3/8" x 5"	50FT	1.17
SKBI55-375-6	3/8" x 6"	50FT	1.41
SKBI55-375-8	3/8" x 8"	50FT	1.88
SKBI55-375-12	3/8" x 12"	50FT	2.83
SKBI55-5-4	1/2" x 4"	50FT	1.25
SKBI55-5-5	1/2" x 5"	50FT	1.57
SKBI55-5-6	1/2" x 6"	50FT	1.88
SKBI55-5-8	1/2" x 8"	50FT	2.51
SKBI55-5-12	1/2" x 12"	50FT	3.77
SKBI55-75-6	3/4" x 6"	50FT	2.84
SKBI55-75-12	3/4" x 12"	50FT	5.66
SKBI55-1-3	1" x 3"	50FT	1.89
SKBI55-1-6	1" x 6"	50FT	3.77
SKBI55-1-8	1" x 8"	50FT	5.02